

Adapters

KS-001
3/8" Snap In Pin



KS-002
1/2" Snap In Pin



KS-003
5/8" Snap In Pin



KS-004
M12 x 30 Stud



KS-005
M10 x 25 Stud



KS-006
M12 x 35 Threaded Socket



KS-007
M10 x 30 Threaded Socket



KS-008
Joining Stud/Swivel



KS-009
150mm Extension



KS-010
Offset Arm 215mm (8.4")



KS-011
100mm Square
Mounting Plate



KS-012
Swivel U Hook



Application:

KS-010 with Convi Clamp



KS-010 with Convi Clamp

KS-014/R
 Camera Stud with 3/8" and 1/4" thread to mount camera directly to with a camera head (Round Shape)



KS-015/R
 Double Female Thread Camera Stud With 3/8" and 1/4" female thread (Round Shape)



KS-016
 90°/45° Joining Stud



KS-017
 Universal 16mm Stud with 3/8" and 1/4" thread



KS-018
 16mm Stud w/M10 thread



KS-019
 Swivel Extension Arm w/5/8" Socket



KS-020/B
 5/8" Compact Alu. Snap In Pin(Black)



KS-023
 3/8" Head mounting plate W/ 5/8" stud



KS-024
 1/4" Head mounting plate W/ 5/8" stud



KS-025
 Camera stud 3/8"-16 thread



KS-026
 Camera stud 1/4"-20 thread



KS-027
 16mm Male Adapter (M10)



KS-052
 Adapter for female thread 3/8"-16 to male 1/4"-20



KD-735P
 Mini Flex Arm With Clip Length 29cm



Application:
 KS-024 with Convi Clamp

KS-053
 Adapter for thread 3/8"-16 to 1/4"-20 (Set for 5 pcs)



KS-030

28mm steel spigot with M10 thread and wing nut, attaches it to lighting yoke then fits into standard lighting stand with 28mm receiver.



KS-032

28mm steel spigot with M12 thread and wing nut, attaches it to lighting yoke then fits into standard lighting stand with 28mm receiver.



KS-034

Solid steel 28mm TV spigot tapped for M10 screw with washer, ideal for mounting lighting fixture directly on to stands or any TV clamps with 28mm receiver.



KS-090 TVMP Adapter

The TV to Motion Picture adapter is designed to attach on the yoke of lighting fixture that can be mounted the stand or fitting into a junior receiver of clamp rigged on the truss.



KS-060

Locking adapter for 5/8" light stand allows vertical or horizontal mounting of a light fixture, flash, or camera that has a 1/4"-20 threaded receptor.



KS-062

Locking adapter for 5/8" light stand allows vertical or horizontal mounting of a light fixture, flash, or camera that has a 3/8" threaded receptor.



KS-070

Female Adapter 16 to 17mm. This is an aluminum female to female adapter. Used to convert a 5/8" male light stand top to a 17mm female socket or to obtain a 17 mm female attachment from 16 mm spigot.



KS-200 Junior to Baby Adapter

This adapter converts 1-1/8" female receiver to 5/8" male stud. Well construction from solid steel with chrome plated. Very helpful to fits into a heavy duty light stands and T.V. clamps or turtle base C stand to mount standard studio flash or video lighting fixtures.



KS-040

28mm steel spigot with a 12cm round mounting plate fits into standard lighting stands or to convert a 28mm receiver to a M10 thread with wing nut.



KS-042

28mm steel spigot with a 12cm round mounting plate fits into standard lighting stands or to convert a 28mm receiver to a M12 thread with wing nut.



KS-080 Ball Race Spigot M10

A rotating 28mm spigot with M10 screw attached. Use this to make a lighting fixture into a follow spot. The smooth panning action is assured by roller bearing inside and a locking knob to control the position.



KS-082 Ball Race Spigot M12

A rotating 28mm spigot with M12 screw attached. Use this to make a lighting fixture into a follow spot. The smooth panning action is assured by roller bearing inside and a locking knob to control the position.



KS-046 3" Baby Wall Plate

This is a 3 x 5" (9x15cm) plate with a 5/8 inch baby stud that extends 3" long. The plate has 8 anchor points for nail or screws which give you plenty of options for mounting anywhere. This may be used on a wall, ceiling, or free-standing as a floor level light mount.



KS-048 Junior Wall Plate

With the same plate size and function as Baby wall plate, but welded with a 4" long 1-1/8" junior receiver for larger lights.



KS-029 Monitor Adapter

(Plate: 75mm x 75mm)



KD-M01P LCD Monitor Arm

Max. Load: 8 kg
Clamping Tube: Dia. 40mm ~ 52mm
Mounting Plate: 75mm x 75mm / 100mm x 100mm




KS-049 Scraper

It is very handy for unusual placements. The 1.1mm thin metal plate for easily jamming into the seams between the door and wall, under a set of books on a bookshelf, held with a sandbag, clamped to a ladder step, in a rock crack, etc. The embossed neck of 16mm baby stud fixed on the plate also designed for firmly hanging small lighting fixture. Additional three anchor points for the screws and nails fixed on the woodenware or ground.



Applications



KCP-230 Griphead
w/ Swivel 5/8" Pin



KCP-310 EZ Grip Finger
The 16mm socket (inside) or 28mm (outside) attached to the ball joint pivots from -45° to 90° while the collar rotates 360° incorporated a 5/8" pin.



KCP-311 EZ Grip Receiver
The 16mm socket attached to the ball joint pivots from -45° to 90° while the collar rotates 360° incorporated a 16mm socket.



KCP-320 EZ Grip Twins
The 5/8" attached to the ball joint pivots from -45° to 90° while the collar rotates 360° incorporated a 5/8" pin.



KCP-340 Baby Plate w/EZ Grip Finger
The square plate attached to the ball joint pivots from -45° to 90° while the collar rotates 360° incorporated another 5/8" pin. (Plate size: 15cm x 9cm)



KCP-330 Tiny Clamp
Steel tiny clamp is ideal for clamping round tube from 2mm to 16mm. Thumbscrew and 1/4" male thread with locking ring for mounting a camera, radio transmitter and lightweight accessories.



KCP-400
Aluminum casting clamp with 5/8" baby receiver for attaching to 35x35mm square pipe.



KCP-420
Aluminum casting clamp with 5/8" baby stud for attaching to 35x35mm square pipe.



Application:
KCP-420 with Lighting fixture



KCP-330 with Max Arm and Camare Flash Light

