

Guide To Symbols



Maximum Height



Maximum Load



Footprint Diameter



Closed Length



Stand Top



Weight



Suggested Caster
(Optional accessory)

Stand Top

All of Kupo lighting stands are available with industry standard top fixings of mounting lighthead and lighting accessories.

T : Compact lightweight aluminum stands with 5/8" (16mm) fixing top and 3/8" -16 screw thread.



A : 5/8" (16mm) fixing light stud



G : Permanently fitted 4 1/2" grip head with additional offset 1 1/8" (28mm) socket.



V : Triple function universal top head with both 1 1/8" (28mm) and 5/8" (16mm) socket. Extra multi direction 5/8" (16mm) light stud.



S : 5/8" (16mm) socket with a detachable 5/8" (16mm) light stud. One end 3/8" -16 and another end 1/4" -20 screw thread.



VJ : Triple function universal top head with both 25mm and 17mm socket. Extra multi direction 16mm light stud. (Japanese Type)

SJ : 17mm socket
(Japanese Type)



A full range of locking mechanisms.



Stand riser column collars are pressure die cast aluminum for strength and incorporate ergonomic locking knobs that hold the light exactly where positioned.

Special Features



Unique bottom spider casting design makes folded stand can be set alone on its own.



The lightweight aluminum stand with aluminum clamping riser which provide a good elasticity. Unlike plastic riser that has memory and result to break.



Bottom spider casting with spring cushioned to prevent jarring of the lamp filament. For those steel stand recited with "spring cushion".



All the aluminum casting knob comes with a mold-in stainless steel bolt for lightweight & long-lasting clamping operation.



Assembled by bolts and nuts for easier maintenance and tightness adjustable instead of fixed rivets.



Baby pin is welded directly to the riser instead of being pinned in steel stand.



Double leg struts for extra strength and stability.



Each KUPO Stand comes with velcro supplied to fasten the legs for better storage and cable management.



The stand leg is equipped with nylon feet to protect both leg and ground.



New innovation compact top head with multi direction 16mm (5/8") light stud.



Leveling leg allows stand keeping vertical in any circumstance.



Ear ring device for wind-bracing kit.




Upper spider casting with extender for hanging sandbag on the center position.



The stainless steel heli-coil insert is equipped inside the aluminum die-casting riser provides a durable threaded hole.



Solid cross pin design in aluminum stand for a better stand stud mount.



A sizable brake shoe to ensure a much better lock off.