

Kupo Pumping Suction Cup offers a temporary solid light mounting solution for smooth, nonporous surfaces. Each Kupo Suction cup comes with 5/8" baby pin or 3/8" thread bolt to allow you to mount small lights or accessories on windows, mirrors, automobiles, boats and any smooth, nonporous surfaces. Because of excellent rubber material with silicon, it can be used at temperatures from -12 degree to 49 degree C. It real pumping in any adverse shooting circumstances

**KSC-01**

9" Suction Cup with 16mm Baby Pin Position the cup pump the handle until the red line is hidden. Check the red line indicator on the plunger frequently. And re-pump it without removing when you find the red line out for safety. Max. Loading: 10KG (22lbs) Weight: 1.05KG (2.3lbs)



**KSC-02**

Double Suction Cup with 16mm Baby Pin Position the cup, push down the handle to remove air from between the rubber pad and the contact surface. Pull the handle vertically and remove the cup when not in use. Max. Loading: 15KG (33.1lbs) Weight: 1.7KG (3.7lbs)



**KSC-03**

6" pumping suction cup with 3/8" -16 thread x 5/8" length stud for use with ball head camera mounts. ( Supplied with pad protector) Max. loading: 32KG( 70 lbs) Weight:0.45 KG( 1 lbs)



**KSC-04**

6" pumping suction cup with fixed baby pin ( Supplied with pad protector) Max. loading: 32KG( 70 lbs) Weight:0.47KG( 1 .1lbs)



**KSC-05**

6" pumping suction cup with swiveling adapter, KS-103, which is detachable. Both ends of adapter come with a ball joint 5/8" (16mm stud); tapped for 3/8" and 1/4" . With pad protector, Max. loading: 4.5KG(9 lbs) Weight:0.7KG( 1.54 lbs)



**KSC-06**

6" pumping suction cup with swivel baby pin which is fixed with cup ( Supplied with pad protector) Max. loading: 20KG( 44 lbs) Weight:1 KG( 2.2lbs)



Application

